

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 19 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.601</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, perpetuated by Stephen F. Turner, Nevada Professional Land Surveyor No. 1803, monumented with an iron pipe, 1 in. diam., 28 ins. long, firmly set, projecting 14 ins. above the ground, with a metal washer attached, mkd. "RLS 1803", as recorded in Clark County, Nevada, File 29 Page 46 Record of Surveys, with a granite stone, 13x11x8 ins., mkd. $\frac{1}{4}$, lying alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R59E S 31 $\frac{1}{4}$ ——— S 6 T19S</p> <p>1991</p> </div> <p>Deposit the original cornerstone, insert the iron pipe inside the stainless steel post and set an orange fiberglass post, $\frac{1}{4}$x3x60 ins., alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°51.3' W., beginning new measurement.</p> <p>Along gravel road.</p>
<p>38.90</p>	<p>Gravel road junction, bears E. and S.</p>
<p>39.174</p>	<p>Point for the cor. of Tps. 18 and 19 S., Rs. 18 and 19 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground to solid rock, and in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R58E R59E S 36 S 31 ——— ——— S 1 S 6 T19S</p> <p>1991</p> </div> <p>From this corner, the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, Tps. 18 S., Rs. 58 and 59 E., monumented with a limestone, 10x8x6 ins., mkd. $\frac{1}{4}$ on the W. face, firmly set, bears N. 2°27.1' W., 40.621 chs. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>