

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 19 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U. S. Deputy Surveyors J. M. Brunt and W. H. Proctor, in 1881</p> <hr/>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2¹/₂ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 19 S., R. 59 E., executed under Group No. 362.</p>
	<p>N. 0°31.0' E., bet. secs. 7 and 12.</p>
	<p>Over rolling land, covered with medium yuccas, cacti, creosote brush, scattered mesquite and joshua trees.</p>
0.10	<p>Gravel road junction, bears N. and E.</p>
29.50	<p>Gravel road junction, bears S. and E.</p>
40.665	<p>The ¹/₄ sec. cor. of secs. 7 and 12, monumented with an iron rebar, ⁵/₈ in. diam., 18 ins. long, set flush with the ground, with an aluminum cap, 1 in. diam., mkd. "DENNIS WISE LS 2379 W ¹/₄ S7". This is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T19S R58E R59E ¹/₄ S 12 S 7 1991</p>
	<p>Insert the iron rebar inside the stainless steel post.</p> <hr/>
	<p>N. 0°30.5' E., beginning new measurement.</p>
	<p>Over rolling land.</p>
40.653	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 8x8x4 ins., mkd. 1 notch on N. edge and 5 notches on the S. edge, firmly set in a mound of stone.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>