

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T16N R30E</td> <td></td> </tr> <tr> <td style="text-align: center;">S 29 S 28</td> <td></td> </tr> <tr> <td style="text-align: center;">-----</td> <td style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S 32 S 33</td> <td></td> </tr> </table> <p style="text-align: center;">1991</p> <p>Set a steel fence post, 5¹/₂ ft. long, alongside the stainless steel post.</p> <p>Land, rolling. Soil, sandy. Undergrowth, greasewood, rabbitbrush, shadscale, Brigham tea and native grass.</p>	T16N R30E		S 29 S 28		-----	-----	S 32 S 33	
T16N R30E									
S 29 S 28									
-----	-----								
S 32 S 33									
	<hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>West, bet. secs. 28 and 33.</p> <p>Over rolling land, through scattered undergrowth.</p>								
<p>40.013</p>	<p>Point for the ¹/₄ sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T16N R30E</td> <td></td> </tr> <tr> <td style="text-align: center;">S 28</td> <td></td> </tr> <tr> <td style="text-align: center;">¹/₄ -----</td> <td></td> </tr> <tr> <td style="text-align: center;">S 33</td> <td></td> </tr> </table> <p style="text-align: center;">1991</p> <p>Set a steel fence post, 5¹/₂ ft. long, alongside the stainless steel post.</p>	T16N R30E		S 28		¹ / ₄ -----		S 33	
T16N R30E									
S 28									
¹ / ₄ -----									
S 33									
<p>80.026</p>	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, sandy. Undergrowth, greasewood, rabbitbrush, shadscale, brigham tea and native grass.</p>								
<p>40.000</p>	<hr/> <p>From the standard cor. of secs. 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the Third Standard Parallel North, through R. 30 E., executed under Group No. 181. Add the marks 1991 to the brass cap.</p> <p>N. 0°03.5' W., bet. secs. 31 and 32.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>Point for the ¹/₄ sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 8 ins. in the ground, over a DEEP-1 magnetic marker, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>								