## SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 27 N., R. 47 E., MDM, NEVADA

	T. 27 N., R. 47 E., MDM, NEVADA
CHAINS	Beginning at the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone projecting 7 ins., with brass cap mkd. as described in the field notes of the independent resurvey of the north boundary of T. 26 N., R. 47 E., executed under Group No. 92.  N. 0°01'30" W., bet. secs. 33 and 34.  Over mountainous land.
40.000	Point for the $^{1}/_{4}$ sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 22 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	T27N R47E
	s 33   s 34
	1994
	Raise a mound of stone, 2 ft. base, $1^1/_2$ ft. high, W. of cor.
	From this corner, a spring bears S. 34 <sup>1</sup> / <sub>4</sub> ° W., 13.70 chs. dist.
58.60	Trail road, bears NE. and SW.
80.000	Point for the cor. of secs. 27, 28, 33 and 34.
00.000	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	T27N R47E S 28 S 27 S 33 S 34
	Set a steel fence post, 5 ft. long, alongside the stainless steel post.
	Land, mountainous in first half mile to nearly level in second half mile. Soil, sandy clay loam. Undergrowth, sagebrush and native grass.
	N. 0°01'30" W., bet. secs. 27 and 28.
	Over nearly level land.
40.000	Point for the $^{1}/_{4}$ sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 20 ins. in the ground, over a plastic incased magnet, with brass cap mkd.