

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 27 N., R. 47 E., MDM, NEVADA

CHAINS	
	<div style="text-align: center;"> T27N R47E  S 4   S 3  <hr style="width: 50%; margin: 0 auto;"/> S 9   S 10    1994 </div> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush and native grass.</p> <hr/> <p>N. 0°01'30" W., bet. secs. 3 and 4.</p> <p>Over nearly level land.</p>
40.000	<p>Point for the ¼ sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a plastic incased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T27N R47E  S 4   S 3    1994 </div>
43.40	<p>Cortez Gold Mining access road, asphalt, bears N. 26½° W. and S. 26½° E.</p>
83.898	<p>Intersect the S. bdy. of sec. 33, T. 28 N., R. 47 E.</p> <p>Point for the closing cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a plastic incased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T28N R47E  S 33  <hr style="width: 50%; margin: 0 auto;"/> S 4   S 3  C C  T27N R47E    1994 </div> <p>From this corner, the cor. of secs. 33 and 34, T. 28 N., R. 47 E., monumented with a stainless steel post, 2½ ins. diam., firmly set projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary of T. 28 N., R. 47 E., executed concurrently under this same Group, bears S. 88°56'40" E., 14.411 chs. dist.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush and native grass.</p> <hr/>