## SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

	T. 27 N., R. 47 E., MDM, NEVADA
CHAINS	T27N R47E
	s 4
	T27N R47E  S 4  1/4 S 9
	1994
	Set a steel fence post, $5^{1}/_{2}$ ft. long, alongside the stainless steel post.
80.004	The cor. of secs. 4, 5, 8 and 9.
	Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush and native grass.
	N. 0°02'10" W., bet. secs. 4 and 5.
:	Over nearly level land.
40.000	Point for the $^{1}/_{4}$ sec. cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	T27N R47E
	s 5   s 4
	1994
	Set a steel fence post, $5^{1}/_{2}$ ft. long, alongside the stainless steel post.
80.000	Point for the 80 $^{1}/_{16}$ sec. cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	1 <sub>/16</sub>
	s 5 s 4 80
	1994
	Set a steel fence post, $5^{1}/_{2}$ ft. long, alongside the stainless steel post.
85.312	Intersect the S. bdy. of sec. 32, T. 28 N., R. 47 E.
	Point for the closing cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a plastic incased magnet, with brass cap mkd.