SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

	T. 27 N., R. 47 E., MDM, NEVADA
CHAINS	Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush and native grass.
	N. 89°41'50" W., bet. secs. 6 and 7.  Over nearly level land.
40.000	Point for the 1/4 sec. cor. of secs. 6 and 7.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, over a plastic incased magnet, with brass cap mkd.
	T27N R47E
	$\frac{1}{4}\frac{s}{s} = \frac{6}{7}$
	1994
	Set a steel fence post, $5^{1}/_{2}$ ft. long, alongside the stainless steel post.
78.866	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 27 N., R. 46 E., executed under Group No. 109.
	Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush and native grass.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°03'00" W., bet. secs. 5 and 6.
	Over nearly level land.
5.561	Intersect line 3-4 of M.S. No. 5087, GAS R64 lode, at a point from which:
	Cor. No. 3 of M.S. No. 5087, GAS R64 lode, identical with Cor. No. 3 of M.S. No. 5087, GAS R65 lode, monumented with an aluminum post, $2^{1}/_{2}$ ins. diam., firmly set projecting 5 ins. above the ground, with aluminum cap mkd. GR64 GR65 3 3 MS5087 1993, bears S. 89°56'37" E., 1.278 chs. dist.
	Cor. No. 4 of M.S. No. 5087, GAS R64 lode, monumented with an aluminum post, $2^{1}/_{2}$ ins. diam., firmly set projecting 5 ins. above the ground, with aluminum cap mkd. GR64 4 MS5087 1993, bears N. 89°56'37" W., 7.813 chs. dist.
40.000	Point for the $^{1}/_{4}$ sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a plastic incased magnet, with brass cap mkd.