DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 28 N., R. 46 E., MDM, NEVADA

	T. 28 N., R. 46 E., MDM, NEVADA
CHAINS	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 16 ins. in the ground to solid rock, over a plastic incased magnet and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	АР
	1994
54.00	Trail road, bears WNW. and ESE.
56.981	The $^{1}/_{4}$ sec. cor. of sec. 30 only, T. 28 N., R. 47 E., hereinafter described.
78.832	Point for the cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point bet. Tps. 28 N., Rs. 46 and 47 E.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 22 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	AP
	1994
	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
 	N. 3°24'10" E., on the E. bdy. of sec. 24.
	Over mountainous land, through scattered sagebrush and native grass.
17.540	The closing cor. of secs. 19 and 30, T. 28 N., R. 47 E., hereinafter described.
19.30	Trail road, bears NW. and SE.
39.416	Point for the 1/4 sec. cor. of sec. 24, at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point bet. Tps. 28 N., Rs. 46 and 47 E.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 20 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	AP
	1994
	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
	From this point, the cor. of Tps. 28 and 29 N., R. 46 E., bears N. 3°24'10" E., 275.912 chs. dist., monumented with a basalt stone in place, 12x12 ins. (Morse's 1901 record, 24x20x20), projecting 10 ins. above the ground, plainly mkd. with a cross (X) on top, T29 on NW. face, R46 on SW. face and 6 notches on the S. and W. edges.