

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 28 N., R. 46 E., MDM, NEVADA

CHAINS

## CORNER POINT NOT REMONUMENTED

from which

A stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground to solid rock, over a plastic incased magnet and in a mound of stone, 3 ft. base to top, for a reference monument, bears S. 41°30' W., 5.02 ft. dist., with brass cap mkd. RM T28N R46E S1 5.02 FT. 1994 and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground to solid rock, over a plastic incased magnet and in a mound of stone, 3 ft. base to top, for a reference monument, bears N. 31°15' W., 5.02 ft. dist., with brass cap mkd. RM T29N R47E S36 5.02 FT. 1994 and an arrow pointing to the cor.

This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 28 N., R. 47 E., MDM, NEVADA

---

Reestablishment of the Survey Executed by  
D. H. Barker and E. C. McClellan, U.S. Deputy Surveyors,  
in 1879,  
and the Resurvey Executed by  
W. H. Good, U. S. Surveyor,  
in 1924

---

From the cor. of secs. 3, 4, 33 and 34, monumented with a porphyry stone, 10x6x5 ins. (Record 15x10x6), firmly set 2 ins. in the ground, plainly mkd. with 3 notches on the E. and W. edges, with a steel fence post exposed 44 ins. alongside. This corner will now refer to the sec. cor. of secs. 33 and 34, T. 28 N., R. 47 E., only.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a plastic incased magnet, with brass cap mkd.

T28N R47E
S 33   S 34

T27N R47E
S 3

1994

Deposit the original cornerstone alongside the stainless steel post.

N. 88°56'40" W., bet. secs. 4 and 33.