

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 28 N., R. 47 E., MDM, NEVADA

CHAINS	<p>N. 89°58'50" W., beginning new measurement, on the S. bdy. of sec. 31.</p> <p>Over nearly level, rolling land.</p>
16.80	Cortez Gold Mining haulage road, bears N. 52¼° W. and S. 52¼° E.
21.745	<p>Intersect line 4-1 of M.S. No. 5087, GAS R14 lode, at a point from which:</p> <p>Cor. No. 1 of M.S. No. 5087, GAS R14 lode, monumented with an aluminum post, 2½ ins. diam., firmly set projecting 2 ins. above the ground, with aluminum cap mkd. G R14 1 MS 5087 1993, bears S. 0°03'23" W., 22.708 chs. dist.</p> <p>Cor. No. 4 of M.S. No. 5087, GAS R14 lode, monumented with an aluminum post, 2½ ins. diam., firmly set projecting 2 ins. above the ground, with aluminum cap mkd. G R14 4 MS 5087 1993, bears N. 0°03'23" E., 0.019 chs. dist.</p>
38.260	The closing cor. of Tps. 27 N., Rs. 46 and 47 E., monumented with an iron post, 3 ins. diam., firmly set in a mound of stone projecting 6 ins., with brass cap mkd. as described in the field notes of T. 27 N., R. 46 E., executed under Group No. 109.
40.110	<p>Point for the 80 1/16 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over a plastic incased magnet, with brass cap mkd.</p> <p style="text-align: center;">1/16 S 31 80</p> <p style="text-align: center;">1994</p>
46.60	Enter mining pit area, bears irregularly E. and W.
78.281	<p>Point for the ¼ sec. cor. of sec. 1, T. 27 N., R. 46 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>POINT NOT MONUMENTED</p>
79.803	<p>Intersect the E. bdy. of T. 28 N., R. 46 E.</p> <p>Point for the closing cor. of Tps. 27 and 28 N., Rs. 46 and 47 E.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the point for the original closing cor., referred to as the SW. cor. of T. 28 N., R. 47 E., in the 1879 survey, and referred to as the old closing cor. of T. 28 N., R. 47 E., in the 1924 survey, determined at record bearing and distance from Cor. No. 1, M.S. No. 4763, Harry C. lode, and rotating the 1941 bearing 2 minutes and 25 seconds to the right to agree with this survey of Mineral Survey No. 4763, bears N. 89°58'50" W., 1.039 chs. dist.</p> <p>POINT NOT MONUMENTED</p> <p>From this same point, the SE. cor. of T. 28 N., R. 46 E., hereinbefore described, bears S. 3°24'10" W., 17.432 chs. dist.</p>