

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 28 N., R. 47 E., MDM, NEVADA

CHAINS	
	N. 87°18'40" W., bet. secs. 19 and 30.
	Over gently rolling land, through scattered sagebrush and native grass.
2.90	Trail road, bears NW. and SE.
6.50	Old abandon mining area.
42.166	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	<p style="text-align: center;">T28N R47E S 19 $\frac{1}{4}$ ————— S 30</p> <p style="text-align: center;">1994</p>
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
	Cor. is located on ridge, bears N. and S.
80.50	Spur, slopes SSW.
84.332	Point for the $80\frac{1}{16}$ sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic incased magnet, with brass cap mkd.
	<p style="text-align: center;">S 19 $\frac{1}{16}$ ————— 80 S 30</p> <p style="text-align: center;">1994</p>
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
127.394	Intersect the E. bdy. of the T. 28 N., R. 46 E.
	Point for the closing cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, $3\frac{1}{2}$ ft. base to top, over a plastic incased magnet, with brass cap mkd.
	<p style="text-align: center;">T28N R46E R47E S 19 ————— CC S 30</p> <p style="text-align: center;">1994</p>