

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 62 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

SC
T41NR62E
1/4 S33

1990

Deposit the original cornerstone and set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Resurvey Executed by
H. Fitzhugh, U. S. Deputy Surveyor,
in 1887

From the amended monument for the standard cor. of Tps. 41 N.,
Rs. 62 and 63 E.

N. 0°31' E., across sec. 31, T. 41 N., R. 63 E., on a blank line.

Over rolling land, covered with dense sagebrush, scattered
bleeding heart, cacti, willows and native grass.

25.20 Pole Creek, 5 lks. wide, 6 ins. deep, course irregularly NE.

40.00 The 1/4 sec. cor. of secs. 31 and 36, monumented with a limestone,
16x14x6 ins., mkd. 1/4 on W. face, firmly set 10 ins. in the ground.
This cor. will now become an amended monument. Add the marks AM
on the original cornerstone and bury in place.

N. 0°29' W., beginning new measurement.

Over rolling land.

20.671 Intersect the line between secs. 30 and 31, T. 41 N., R. 63 E., at
a point from which the cor. of secs. 30 and 31, monumented with a
stainless steel post, 2 1/2 ins. diam., firmly set showing 4 ins.
above ground, with brass cap mkd. as described in the field notes
of T. 41 N., R. 63 E., executed concurrently under this same
Group, bears N. 88°56' W., 3.658 chs. dist.

Continue measurement across sec. 30, T. 41 N., R. 63 E., on a
blank line.

40.05 The cor. of secs. 25, 30, 31 and 36, monumented with a limestone,
8x6x6 ins., dimly mkd. with 5 notches on N. edge and 1 notch on S.
edge, firmly set 4 ins. in the ground, with a mound of stone to
the W. This cor. will now refer to the southeast cor. of sec. 25
only.