

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
48.02	<p>The Maxson cor. of Tps. 41 and 42 N., R. 63 E., monumented with a limestone, 16x7x4 ins., plainly mkd. with 6 notches on N., S. and E. edges, firmly set 8 ins. in the ground, bears WEST, 2.14 chs. dist. This cor. will now become an amended monument. Add the marks AM on the cornerstone and bury in place.</p>
59.204	<p>The closing cor. of Tps. 41 and 42 N., R. 63 E., monumented with a stainless steel post, 2¹/₂ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 41 N., R. 63 E., executed concurrently under this same Group.</p>
59.80	<p>Power line, bears N. 32¹/₄° E. and S. 32¹/₄° W.</p>
60.585	<p>Point for the N ¹/₁₆ sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T41N R62E R63E N ¹/₁₆ S1 </p> <p>1990</p> </div> <p>Set a steel fence post, 5¹/₂ ft. long, alongside the stainless steel post.</p>
60.70	<p>Swale, bears NE. and SW.</p>
80.78	<p>The cor. of Tps. 41 and 42 N., R. 62 E., monumented with a limestone, 12x6x4 ins., plainly mkd. with 6 notches on N., S., and W. edges and improperly mkd. with CC on E. face, firmly set 6 ins. in the ground, with steel fence post, 5¹/₂ ft. long, set 1¹/₂ ft. in the ground alongside, with a wood post, 1 in. diam., 18 ins. long, wired to the steel fence post.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T42N R62E R63E S36 ----- S31 S1 T41N </p> <p>1990</p> </div> <p>Deposit the original cornerstone and reset the wood post and steel fence post alongside the stainless steel post.</p> <hr/>