

DEPENDENT AND INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The point for the N $\frac{1}{4}$ sec. cor. of sec. 6, is on the Eighth Standard Parallel North and at proportionate distance on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T41N R64E <hr/> $\frac{1}{4}$ S 6 T40N R64E</p> <p style="text-align: center;">1989</p> <p>From this corner, the standard cor. of Tps. 41 N., Rs. 63 and 64 E., hereinbefore described, bears N. $89^{\circ}08'$ W., 12.44 chs. dist.</p> <hr/> <p style="text-align: center;">Reestablishment of the Resurvey and Survey Executed by H.B. Maxson, U.S. Deputy Surveyor, in 1894</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. N. $4^{\circ}01'$ E., bet. secs. 35 and 36.</p> <p>Over mountainous land, covered with scattered juniper, sagebrush and native grass.</p> <p>29.30 Spur, slopes SE.</p> <p>35.40 Ravine, drains SE.</p> <p>41.42 The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a limestone, 16 x 8 x 5 ins., plainly mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone, alongside a No. 5 rebar, 18 ins. long, firmly set showing 8 ins. above ground, with a metal washer mkd. "RLS 3921", wired to the rebar. (Record: redwood post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R64E <hr/> $\frac{1}{4}$ S 35 S 36</p> <p style="text-align: center;">1989</p> <p>Insert the rebar inside the stainless steel post and deposit the original cornerstone alongside the stainless steel post.</p> <hr/> <p>N. $0^{\circ}38'$ E., beginning new measurement.</p> <p>Over mountainous land.</p>
--------	--