DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, TOWNSHIP 42 NORTH, RANGE 64 EAST, MDM, NEVADA

CHAINS 79.59

The cor. of Tps. 41 and 42 N., Rs. 63 and 64 E., monumented with a juniper post, 2 ins. square, 15 ins. long, with illegible scribe marks visible, firmly set alongside a steel fence post.

At the corner point

Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

> **T42N** R63E R64E s 36 s 31 1 S **T41N**

> > 1989

Reset the original wooden post and steel fence post alongside the stainless steel post.

From this corner, U.S.C. & G.S. triangulation station "RED POINT", monumented with a standard brass tablet set in the top of a concrete monument, 6 ins. diam., exposed 4 ins. above the ground, with brass tablet mkd. RED POINT 1940, bears N. 42°59'30" W., (mean bearing) 73.79 chs. dist.

> DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 41 N., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by A. J. Hatch and J. H. Eaton, U.S. Deputy Surveyors, in 1870

From the standard cor. of Tps. 41 N., Rs. 63 and 64 E., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 40 N., R. 64 E., executed concurrently under this same Group.

N. 0°48' E., bet. secs. 31 and 36.

Over rolling reseeded land, through scattered sagebrush and crested wheatgrass.

39.94 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

> Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.