

T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The geographic position for the southeast corner of section 34, is at latitude $36^{\circ} 04' 17.85''$ N. and longitude $114^{\circ} 55' 12.11''$ W. (NAD 27), as calculated from a direct tie to U.S.G.S. triangulation station "RMT 7 (USBR)".

The magnetic declination is 15° E., as shown on U.S.G.S. 7.5 minute quadrangle map "HENDERSON, NEV." dated 1970.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
T. A. Magee, U. S. Deputy Surveyor, in 1883,
and
the Resurvey by C. S. Swanholm, U. S. Cadastral Engineer,
in 1931

From the $\frac{1}{4}$ sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 22 S., R. 63 E., executed under Group No. 169. Add the marks "T21SR63E 1991" to the brass cap.

N. $89^{\circ}55'$ W., on the S. bdy. of sec. 34.

Over rolling land, covered with scattered creosote brush and cacti.

8.497 The $\frac{1}{4}$ sec. cor. of sec. 3 only, T. 22 S., R. 63 E., monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 22 S., R. 63 E., executed under Group No. 169. Add the marks "T22SR63E 1991" to the brass cap. This corner is located on a spur, slopes NNW.

20.230 Point for the W $\frac{1}{16}$ sec. cor. of sec. 34 only.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.

W $\frac{1}{16}$ S 34

1991

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. This corner is located in a wash, 3 chs. wide, 2 ft. deep, drains NW.

36.30 Double metal tower transmission line, bears N. $3\frac{3}{4}^{\circ}$ W. and S. $3\frac{3}{4}^{\circ}$ E.