

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

40.460

The cor. of secs. 33 and 34 only, monumented with an iron post, 2 ins. diam., firmly set showing 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 22 S., R. 63 E., executed under Group No. 169.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
T. A. Magee, U. S. Deputy Surveyor, in 1883  
and  
the Resurvey by E. Voigt, Associate Cadastral Engineer  
and J. W. Hardison, Assistant Cadastral Engineer, in 1943

From the cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set in a collar of stone, with brass cap mkd. as described in the field notes of T. 21 S., R. 63 E., executed under Group No. 336.

N. 2°25' E., bet. secs. 25 and 26.

Over mountainous land, covered with scattered creosote brush and cacti.

20.237

Point for the S  $\frac{1}{16}$  sec. cor. of secs. 25 and 26.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock, over a DEEP-1 magnetic marker and in a mound of stone, 6 ft. base to top, with brass cap mkd.

S  $\frac{1}{16}$

S 26 | S 25

1991

40.474

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 21 S., R. 63 E., executed under Group No. 336. Add the marks "T21SR63E 1991" to the brass cap.

N. 2°25' E., beginning new measurement.

Over mountainous land.

4.20

Spur, slopes W.

11.20

Double wood pole transmission line, bears N. 51 $\frac{1}{2}$ ° E. and S. 51 $\frac{1}{2}$ ° W.

20.237

Point for the N  $\frac{1}{16}$  sec. cor. of secs. 25 and 26.