

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.</p> $\begin{array}{r} \text{S } 27 \\ \text{E } \frac{1}{16} \text{ ---} \\ \text{S } 34 \end{array}$ <p>1991</p>
40.166	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>The ¹/₄ sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set showing 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 21 S., R. 63 E., executed under Group No. 336. Add the marks "T21SR63E 1991" to the brass cap.</p> <hr/> <p>S. 89°49' W., beginning new measurement.</p> <p>Over rolling land.</p>
20.110	<p>Point for the W ¹/₁₆ sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.</p> $\begin{array}{r} \text{S } 27 \\ \text{W } \frac{1}{16} \text{ ---} \\ \text{S } 34 \end{array}$ <p>1991</p>
31.50	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Double metal tower transmission line, bears N. ³/₄° W. and S. ³/₄° E.</p>
33.80	<p>Improved gravel road, bears NNW. and SSE.</p>
34.70	<p>Enter borrow pit, edge bears irregularly N. and S.</p>
40.220	<p>The cor. of secs. 27, 28, 33 and 34.</p>
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF M.S. No. 4743, T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of the Survey Executed by R. L. Motz, Mineral Surveyor, in 1938</p> <hr/>	
<p>From Cor. No. 1 of M.S. No. 4743, Hydro lode, identical with Cor. No. 1 of M.S. No. 4743, Hydro No. 1 lode, and Cor. No. 2 of M.S. No. 4743, Cuna lode, determined at record distances from the original bearing objects:</p>	