

SUBDIVISION OF SECTION 34,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a steel fence post, 4 ft. long, alongside the stainless steel post.
10.80	Spur, slopes NW.
20.424	Point for the NW $\frac{1}{16}$ sec. cor. of sec. 34, at intersection with the E-W center line of the NW $\frac{1}{4}$ .
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, over a DEEP-1 magnetic marker, with brass cap mkd.
	NW $\frac{1}{16}$ S 34
	1991
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
40.851	The W $\frac{1}{16}$ sec. cor. of secs. 27 and 34.
	From the C-N $\frac{1}{16}$ sec. cor. of sec. 34.
	S. 89°41' W., on the E-W center line of the NW $\frac{1}{4}$ of sec. 34.
	Over rolling land, covered with scattered creosote brush and cacti.
7.10	Spur, slopes N.
18.00	Spur, slopes N.
20.142	The NW $\frac{1}{16}$ sec. cor. of sec. 34.
27.60	Improved gravel road, bears NW. and SE.
32.70	Double metal tower transmission line, bears N. $\frac{3}{4}$ ° W. and S. $\frac{3}{4}$ ° E.
40.275	The N $\frac{1}{16}$ sec. cor. of secs. 33 and 34.
	METES-AND-BOUNDS SURVEY OF A PORTION OF THE NORTHERLY RIGHT-OF-WAY OF LAKE MEAD DRIVE, T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the witness point on the section line bet. secs. 25 and 26, hereinbefore described, from which the cor. of secs. 23, 24, 25 and 26, bears N. 2°25' E., 5.450 chs. dist.
	Thence S. 18°19' W.
8.728	Beginning of curve, point not monumented.
	Thence along the arc of a circular curve to the right having a radius of 3,250 ft.; the chord of said arc bears S. 24°10' W., 10.038 chs. dist.