DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of a Portion of the Survey Executed by U. S. Deputy Surveyors J. M. Brunt and W. H. Proctor in 1881
	From the standard cor. of Tps. 24 S., Rs. 59 and 60 E., remonumented by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, monumented with a rebar, $\frac{5}{8}$ in. diam., 18 ins. long, firmly set flush with the ground, with an aluminum cap, 2 ins. diam., mkd. "NEVADA POWER COMPANY RLS 6199 59 60" and a limestone, 11x10x7 ins., mkd. with 6 notches on the E. and W. edges and 6 grooves on the N. face, lying alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T24S R59E R60E S 36 S 31
	1992
	Deposit the original cornerstone alongside the stainless steel post and insert the rebar inside the stainless steel post.
	From this corner, U. S. C. & G. S. triangulation station "GAUGE", monumented with an iron pipe, $^{1}/_{4}$ in. diam., set in concrete, in drill hole on rock outcrop, bears N. 72°49.5′ E. (MEAN BEARING), 26.348 chs. dist.
	From this same corner, Nevada State Department of Highways station, monumented with a brass disc, 3 ins. diam., firmly set flush in ground in concrete, mkd. "Sta 'W' 'E' 119 + 66.19 P.O.T. Dist. 54.00 Angle 90 Date set 9-59," bears S. 84°04.9' W., 11.275 chs. dist.
	N. 89°32.8' W., on the S. bdy. of sec. 36.
	Over gently rolling land, covered with scattered creosote brush, yuccas, various cacti and native grass.
6.00	Intersect I-15 right-of-way, fence, bears N. 30°53' E. and S. 30°53' W.
8.576	The closing cor. of Tps. 25 S., Rs. 59 and 60 E., hereinafter described.
9.50	East bound lane, I-15, bears N. 31° E. and S. 31° W.
11.40	West bound lane, I-15, bears N. 31° E. and S. 31° W.
14.93	Intersect I-15 right-of-way, fence, bears N. 30°53' E. and S. 30°53' W.