DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA

	MOUNT DIRELO MERIDIRA, NEVADA
CHAINS	N. 89°54.8' W., on the S. bdy. of sec. 35.
	Over gently rolling land, covered with scattered creosote brush, yuccas, various cacti and native grass.
8.608	The closing cor. of secs. 1 and 2, T. 25 S., R. 59 E., hereinafter described.
40.600	The standard 1 / ₄ sec. cor. of sec. 35, monumented with a limestone, 13x8x5 ins., mkd. 1 / ₄ on the N. face, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$ \begin{array}{c} S C \\ T24S R59E \\ {}^{1}/_{4} S 35 \\ \end{array} $
	1992
	Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 25 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by U. S. Deputy Surveyor T. A. Magee in 1883
	From the cor. of Tps. 25 and 26 S., Rs. 59 and 60 E., remonumented by Jack Parvin, Nevada Professional Land Surveyor No. 286, monumented with a rebar, $5/_8$ in. diam., 18 ins. long, firmly set in a deeply embedded mound of stone, with a plastic cap stamped "JACK PARVIN RLS 286", with decayed remains of a wooden post scattered in the mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25S R59E R60E S 36 S 31
	S 1 S 6 T26S
	1992