DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 25 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	1. 23 S., K. 39 E., MOUNT DIABLO MERIDIAN, NEVADA
14.95	Intersect I-15 right-of-way, fence, bears N. 30°52' E. and S. 30°52' W.
20.280	Point for the W $^{1}/_{16}$ sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 26 ins. in the ground, with brass cap mkd.
	$W^{-1}/_{16} = \frac{s-1}{s-12}$
	W 1/16 S 12
	1992
	Set a steel fence post, 6 ft. long, alongside the stainless steel post.
40.560	The cor. of secs. 1, 2, 11 and 12.
	N. 0°02.6' W., bet. secs. 1 and 2.
	Over gently rolling land, covered with scattered creosote brush, yuccas, various cacti and native grass.
39.718	Point for the $^{1}/_{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25S_R59E
	s 2 s 1
	1992
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
40.50	Trail road, bears NE. and SW.
81.770	The closing cor. of secs. 1 and 2, determined by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, monumented with a rebar, $\frac{5}{8}$ in. diam., 18 ins. long, set flush with the ground, with an aluminum cap, 2 ins. diam., mkd. "NEVADA POWER COMPANY RLS 6199". This rebar is accepted as the best available evidence of the position of the original corner. Add the marks "AM BLM 1992" to the aluminum cap.
81.878	Intersect the Sixth Standard Parallel South.
	Point for the closing cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, with brass cap mkd.