## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 10 M., R. 27 B., MOUNT DIABLE MEXIDIAN, NEVADA
CHAINS	Reestablishment of a Portion of the Survey Executed by T. A. Magee and W. F. Reilly, U.S. Deputy Surveyors, in 1881
	From the $^{1}/_{4}$ sec. cor. of secs. 15 and 22, monumented with a basalt stone, 24x13x3 ins., plainly mkd. $^{1}/_{4}$ on N. and S. faces, firmly set in a mound of stone. This cor. will now refer to the $^{1}/_{4}$ sec. cor. of sec. 15 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T16N R29E  1/4 S15
,	1996
	Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 3 ft. high, N. of cor.
	S. 89°47′40" W., on the S. bdy. of sec. 15.
	Over mountainous land, covered with scattered shadscale, cacti, Brigham tea and native grass.
6.70	Ridge, bears N. and S.
16.90	Spur, slopes SW.
24.392	The closing cor. of secs. 21 and 22, hereinafter described.
33.30	Wash, 75 lks. wide, 3 ft. deep, drains S. 25° W.
40.106	The cor. of secs. 15, 16, 21 and 22, monumented with a basalt stone, 19x9x6 ins., plainly mkd. with 3 notches on E. and W. edges, firmly set in a mound of stone, with a wood post, 4 ins. square, 4 ft. long, set alongside. This cor. will now refer to the cor. of secs. 15 and 16 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T16N R29E S16 S15
	<b>S21</b>
	1996
	Deposit the original cornerstone and reset the wood post, alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	S. 89°26'30" W., on the S. bdy. of sec. 16.