

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.

T16N  
R28E R29E  
S13 | S18

S24  
T16N R28E

1996

Insert the rebar inside the stainless steel post and deposit the original cornerstone alongside the stainless steel post.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4813,  
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
E. P. Osgood, U.S. Mineral Surveyor, in 1951

From Cor. No. 1 of M.S. No. 4813, Kesilgore Placer, monumented with the decayed remains of base of rotted post, firmly set in a mound of stone, with the remaining piece of the post, 4 ins. squared, 5 ft. 9 ins. long, mkd. 4813 on one side and COR NO. 1 on another side, lying on the mound of stone.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

K  
COR-1  
MS 4813 | S29

T16N R29E

1996

Deposit the original wood post alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, NW. of cor.

Thence N. 0°01'50" E.

40.013

Cor. No. 2 of M.S. No. 4813, Kesilgore Placer, monumented with a deeply embedded mound of stone. This mound of stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.