DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4813, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS 26.562	Intersect the line bet. secs. 29 and 30, hereinafter described.
31.00	Ravine, drains SE.
39.968	Cor. No. 1 of M.S. No. 4813, Kesilgore Placer, and place of beginning.
	SURVEY OF A PORTION OF THE WEST BOUNDARY, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the standard cor. of Tps. 16 N., Rs. 28 and 29 E., monumented with an iron post, 3 ins. diam., firmly set in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of the Third Standard Parallel North through Range 29 East, executed under Group No. 181.
	North, bet. secs. 31 and 36.
	Over mountainous land.
13.70	Spur, slopes ESE.
36.10	Spur, slopes E.
40.000	Point for the $^{1}/_{4}$ sec. cor. of secs. 31 and 36, falls on N. side of large basalt boulder in rock slide on steep hillside, where it is impracticable to establish a permanent monument.
40.050	Point selected for the witness cor. to the $^{1}/_{4}$ sec. cor. of secs. 31 and 36.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	WC T16N R28E R29E 1/4 S36 S31
	1996
	Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
50.60	Trail road in bottom of canyon, bears ENE. and WSW.
71.60	Spur, slopes SSW.
80.000	Point for the cor. of secs. 25, 30, 31 and 36.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	•