SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this corner, the $^{1}/_{4}$ sec. cor. of sec. 18 only, hereinbefore described, bears N. 89°16′10" W., 14.180 chs dist.
	DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 5123, TPS. 16 N., RS. 28 AND 29 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by L.D. Emery, U.S. Mineral Surveyor, in 1994
	From Cor. No. 1 of M.S. No. 5123, POPCORN No. 1 lode, identical with Cor. No. 1 of M.S. No. 5123, POPCORN No. 2 lode, monumented with an aluminum post, 1 in. diam., firmly set in concrete in a mound of stone, with an aluminum cap, $3^{1}/_{4}$ ins. diam., mkd.
	USMS 5123
	1 PC 2 1 PC 1
	Thence N. 89°55'00" E.
0.149	Intersect the line bet. secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
7.00	Improved gravel road, bears NE. and SW.
9.091	Cor. No. 2 of M.S. No. 5123, POPCORN No. 1 lode, monumented with an aluminum post, 1 in. diam., firmly set in concrete, with an aluminum cap, $3^{1}/_{4}$ ins. diam., mkd.
	USMS 5123
	2 PC 1
	2 FG 1
	Thence S. 0°03'00" E.
10.00	Wash, drains irregularly N.
11.360	The true point for Cor. No. 3 of M.S. No. 5123, POPCORN No. 1 lode, determined by extending the line through the witness cor. and at record distance, falls in wash, occupied by an unmarked wood post, 2 ins. squared, firmly set in a mound of stone, exposed 3 ft. above the ground.
	Thence S. 89°58'10" W.
0.30	Wash, drains irregularly N.
1.061	The witness cor. to Cor. No. 3 of M.S. 5123, POPCORN No. 1 lode, monumented with an aluminum post, 1 in. diam., firmly set in concrete in a mound of stone, with an aluminum cap, $3^1/_4$ ins. diam., mkd.