DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 29 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 29 N., R. 48 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of the Survey Executed by E. B. Monroe and E. C. McClellen in 1881 and the Dependent Resurvey Executed by J. A. Bastian and R. K. Baugh in 1978
	Beginning at the $^1/_4$ sec. cor. of secs. 4 and 9, monumented with an iron post, $2^1/_2$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1978 resurvey.
	N. 89°17' W., bet. secs. 4 and 9.
37.946	Intersect a fence which bears N-S; point for a witness point.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	WP S4
	s9
	1996
	From this corner the corner of fences projecting N and W bears S. 0°50' E., 94 lks. dist.
40.174	The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, $2^{1}/_{2}$ ins. diam., firmly set, projecting 4 ins above the ground, with brass cap mkd. as described in the field notes of the 1978 resurvey, and a mound of stone west of the corner.
	N. 1°29' E., bet. secs. 4 and 5.
40.660	The 1 / $_{4}$ sec. cor. of secs. 4 and 5, monumented with an iron post, 2^{1} / $_{2}$ ins. diam., firmly set 6 ins. below the surface of a graded road which bears E-W, with brass cap mkd. as described in the field notes of the 1978 resurvey; there is no remaining evidence of the reference monuments set in 1978.
	N. 1°29' E., beginning new measurement.
40.996	The cor. of secs. 4 and 5, on the north boundary of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1914 resurvey executed by W. A. Pray.
	Corner is located at the corner of fences projecting S and E.