DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Reestablishment of the Survey Executed by U. S. Deputy Surveyor Butler Ives in 1861
	From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with a basalt stone, 22x12x9 ins., plainly mkd. with 5 notches on the E. side and 1 notch on the W. side, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SC T16N R22E S31 | S32 1995
	Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	S. 89°48'00" W., on the S. bdy. of sec. 31.
	Over rolling land, covered with medium sagebrush, rabbitbrush, native grasses, scattered pinon pine and juniper.
1.10	Abandoned trail road, bears NW. and SE.
7.00	Draw, drains irregularly NW.
8.10	Improved gravel road, bears NNW. and SE.
13.70	Single pole power line, bears N. $34^3/_4$° W. and S. $34^3/_4$° E.
40.210	The standard $^1/_4$ sec. cor. of sec. 31, monumented with a basalt stone, 21x12x8 ins., mkd. $^1/_4$ on N. face, firmly set in a mound of stone.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, 3 ft. base, with brass cap mkd.
	SC T16N R22E 1/4 S31 1995
	Deposit the original cornerstone alongside the stainless steel post.
	N. 89°47'50" W., beginning new measurement.