

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 16 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

concrete cylinder, 11 ins. diam., exposed 3 ins., mkd. "DAYTON  
1951", bears N. 89°49'58" W. (mean bearing), 146.03 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 16 N., R. 22 E., MOUNT DIABLO MERIDIAN NEVADA

Reestablishment of the Survey Executed by  
U. S. Deputy Surveyor W. H. Craigue in 1911

From the cor. of secs. 19, 20, 29 and 30, monumented with an iron  
post, 2 ins. diam., firmly set showing 10 ins. above the ground,  
with brass cap mkd. as described in the field notes of T. 16 N.,  
R. 22 E., executed under Group No. 13.

Corner is located at corner of fences, bearing N. and W.

N. 89°56'40" W., bet. secs. 19 and 30.

Over gently rolling land, covered with medium sagebrush,  
rabbitbrush and native grasses.

39.938

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, monumented with a rebar,  
 $\frac{5}{8}$  in. diam., 16 ins. long, firmly set showing 8 ins. above the  
ground, with the original iron post, 1 in. diam., wired to the  
rebar, with brass cap mkd. as described in the field notes of  
T. 16 N., R. 22 E., executed under Group No. 13.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins.  
in the ground, over a plastic-encased magnet and in a collar of  
stone, 3 ft. base, with brass cap mkd.

T16N R22E

S19

$\frac{1}{4}$  ——— .

S30

1995

Invert and insert the original iron post and rebar inside the  
stainless steel post.

S. 89°58'00" W., beginning new measurement.

36.00

Corner of fences, bearing E., SSE. and W.

40.315

The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 16 N., R. 22 E., MOUNT DIABLO MERIDIAN, NEVADA

From the standard cor. of secs. 31 and 32, on the S. bdy. of the  
Tp.