307

## DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by R.H. Woods and W.H. Myrick in 1881 and the Dependent Resurvey Executed by C.S. Swanholm in 1930-33  Beginning at the corner of sections 12 and 13, T. 19 S., R. 62 E., monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes of the 1930-33 resurvey, and a mound of stone west of the corner; add the marks 1993 to the cap. N. 0°18.4' W., on the east boundary of section 12.  8.25 Railroad track, bears NE. and SW.  Intersect the southerly boundary of a utility right-of-way corridor, bears N. 73°13.1' E. Point for a witness point on the east boundary of section 12.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 4 ft. base to top, with brass cap marked:  WP N52787  S12 S 7 R62E R63E T19S  1993  21.90 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes of the 1930-33 resurvey, and a mound of stone east of the corner;
monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes of the 1930-33 resurvey, and a mound of stone west of the corner; add the marks 1993 to the cap.  N. 0°18.4′ W., on the east boundary of section 12.  8.25 Railroad track, bears NE. and SW.  9.922 Intersect the southerly boundary of a utility right-of-way corridor, bears N. 73°13.1′ E.  Point for a witness point on the east boundary of section 12.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 4 ft. base to top, with brass cap marked:  WP  N52787  S12 S 7  R62E R63E  T19S  1993  21.90 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
Railroad track, bears NE. and SW.  9.922 Intersect the southerly boundary of a utility right-of-way corridor, bears N. 73°13.1′ E.  Point for a witness point on the east boundary of section 12.  Set a stainless steel post, 28 ins. long, 2¹/2 ins. diam., 10 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 4 ft. base to top, with brass cap marked:  WP  N52787  S12  R62E  R63E  T19S  1993  21.90 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  23.92 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  26.33 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  27.87 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
Intersect the southerly boundary of a utility right-of-way corridor, bears N. 73°13.1′ E.  Point for a witness point on the east boundary of section 12.  Set a stainless steel post, 28 ins. long, 2¹/2 ins. diam., 10 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 4 ft. base to top, with brass cap marked:  WP  N52787  S12  S7  R62E  R63E  T19S  1993  21.90  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  23.92  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
corridor, bears N. 73°13.1′ E.  Point for a witness point on the east boundary of section 12.  Set a stainless steel post, 28 ins. long, 2¹/2 ins. diam., 10 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 4 ft. base to top, with brass cap marked:  WP  N52787  S12  S7  R62E  R63E  T19S  1993  21.90  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 10 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 4 ft. base to top, with brass cap marked:  WP  N52787  S12 S 7  R62E R63E  T19S  1993  21.90 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  23.92 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  26.33 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  27.87 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 4 ft. base to top, with brass cap marked:  WP  N52787  S12  R62E  R63E  T19S  1993  21.90  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  23.92  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  26.33  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  27.87  Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  37.394  The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
N52787  S12 S 7  R62E R63E  T19S  1993  21.90 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  23.92 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  26.33 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  27.87 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
S12 S 7 R62E R63E T19S  1993  21.90 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  23.92 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  26.33 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  27.87 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
R62E R63E T19S  1993  21.90 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  23.92 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  26.33 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  27.87 Power transmission line, bears N. 73°13.1′ E. and S. 73°13.1′ W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
21.90 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. 23.92 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. 26.33 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. 27.87 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W. 37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  23.92 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  26.33 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  27.87 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  26.33 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  27.87 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
26.33 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  27.87 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
27.87 Power transmission line, bears N. 73°13.1' E. and S. 73°13.1' W.  37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
37.394 The 1/4 section corner of section 7, T. 19 S., R. 63 E., monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes
remark the cap to read as follows:
T19S R62E   R63E   1/4   S 7   1993   1933
38.364 Intersect the northerly boundary of a utility right-of-way corridor, bears N. 73°13.1′ E.
Point for a witness point on the east boundary of section 12.