## $342^{2}$

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 18 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 18 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of the Survey Executed by C.S. Swanholm in 1930-33
	Beginning at the corner of sections 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes of the 1930-33 survey, and a mound of stone W. of the corner; add the marks 1993 to the cap.
	S. 89°57.7' W., between sections 2 and 35, on the northerly boundary of a utility right-of-way corridor.
39.969	The $1/4$ section corner of sections 2 and 35, monumented with an iron post, 1 in. diam., projecting 4 ins. above the ground, with brass cap marked as described in the field notes of the 1930-33 survey, and a mound of stone N. of the corner; remark the cap to read as follows:
	T18S R63E
	S35
	1/4
	S 2
	T195
	1993 1933
	1932
	S. 89°58.0' W., beginning new measurement.
35.162	Intersect the easterly right-of-way of Interstate Highway No. 15.
	Point for a witness point between sections 2 and 35.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 20 ins. in the ground, over a DEEP-1 magnetic marker and in a collar of stone, with brass cap marked:
	WP
	T18S
	R63E
	ROW / S35
	115 / S 2
	R63E
	T19S
	1993
	From this witness point a Nevada Highway Department station, monumented with a standard brass tablet, set in concrete, flush with the surface of the ground, marked OE821+38.91POT DIST 57.41 ANGLE 90, bears N. 19°01.7' E., 8.820 chs. dist.
40.011	Point for the corner of sections 2, 3, 34 and 35 at proportionate distance; there is no remaining evidence of the original corner.
	Set a brass tablet, $3^{1}/_{4}$ ins. diam., $3^{1}/_{2}$ in. stem, in concrete, over a rebar, 5/8 in. diam., 18 ins. long, flush with the surface of the ground at the easterly edge of the pavement of the southbound lanes of Interstate Highway No. 15, with top marked:
Contraction of the local division of the loc	