DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 18 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA CHAINS True point for the l_{4} section corner of sections 30 and 31 at 0.981 proportionate distance. 30.754 The closing corner of sections 30 and 31, monumented with an iron post, 2 ins. diam., set in a mound of stone, with brass cap marked as described in the field notes of the 1930-33 survey. from which the original bearing objects A cross (X) chiseled on a limestone ledge, bears S., $13^{1}/_{2}$ lks. dist. A limestone ledge, bears S. 70° W., 37^{1}_{2} lks. dist., marked X BO S36 (record S. 78°57' W., 35^{1}_{2} lks.). Add the marks 1993 to the cap. From the corner of sections 29, 30, 31 and 32. N. 0°01.3' E., between sections 29 and 30. 3.72 Underground gas pipeline, bears NE. and SW. 7.547 Intersect the southerly boundary of a utility right-of-way corridor, bears N. 19°47.5' E. and S. 19°47.5' W. Point for a witness point between sections 29 and 30. Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 8 ins. in the ground, over a DEEP-1 magnetic marker and in a mound of stone, 3 ft. base to top, with brass cap marked: WP N52787 **S**30 S29 T185 R63E 1993 From this witness point a witness point at the intersection of the easterly boundary of a utility right-of-way corridor with the line between sections 30 and 31, hereinbefore described, bears S. 19°47.5' W., 8.021 chs. dist. From this same witness point the point of intersection of utility corridor rights-of-way bears N. 19°47.5' E., 22.454 chs. dist. Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker and in a collar of stone, with brass cap marked: