DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 18 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

T. 18 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA CHAINS 17.91 Power transmission line, bears N. 10°01.6' E. and S. 10°01.6' W. Intersect the westerly boundary of a utility right-of-way 18.679 corridor, bears N. 10°01.6' E. and S. 10°01.6' W. Point for a witness point between sections 5 and 8. Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a DEEP-1 magnetic marker with brass cap marked: WP **T18S** R63E N52787 1993 From this witness point a witness point at the intersection of the westerly boundary of a utility right-of-way corridor with the line between sections 5 and 32, monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., set 4 ins. below the surface of a road, with brass cap marked as described in the field notes of the concurrent resurvey of a portion of the south boundary of T. 17 S., R. 63 E., bears N. 10°01.6′ E., 84.410 chs. dist. 39.953 The corner of sections 5, 6, 7 and 8, monumented with an iron post, 3 ins. diam., projecting 8 ins. above the ground, with brass cap marked as described in the field notes of the 1930-33 survey, and a mound of stone W. of the corner; add the marks 1993 to the cap. SUBDIVISION OF SECTION 8, T. 18 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA From the $^{1}/_{4}$ section corner of sections 8 and 17, monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, with brass cap marked as described in the field notes of the 1930-33 survey, and a mound of stone N. of the corner; remark the cap to read as follows: T18S R63E s 8 1/4 -**S17** 1993 1933 N. 0°02.6' E., on the N-S center line of section 8. 40.013 Point for the center 1/4 section corner at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 22 ins. in the ground, over a DEEP-1 magnetic marker with brass cap marked: