

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 17 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by
R.H. Woods and W.H. Myrick in 1882
and the Dependent Resurvey Executed by
C.S. Swanholm in 1930-33


Beginning at the corner of sections 3, 4, 33 and 34, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 63 E., executed by C.P. Sylvester in 1958, and a mound of stone south of the corner; add the marks 1993 to the cap.

From this corner, National Geodetic Survey triangulation station "BIBLE", monumented with a standard U. S. C. & G. S. brass tablet, marked BIBLE 1957, cemented in a drill hole in a rock in place, bears N. 74°17.8' E., 44.858 chs. dist.

N. 89°24.3' W., between sections 4 and 33.

- 17.993 Intersect the centerline of U.S. Highway No. 93, bears N. 44°07.8' W. and S. 44°07.8' E.
- 22.10 Telephone cable, underground, parallels U.S. Highway No. 93.
- 22.259 Point selected for a witness point on line between sections 4 and 33 at intersection with the southerly right-of-way of U.S. Highway No. 93.

Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 20 ins. in the ground, over a DEEP-1 magnetic marker with brass cap marked:



1993

From this witness point a Nevada Highway Department station, monumented with a standard brass tablet, set in concrete, 4 ins. below the surface of the ground, marked C 207+22.81 POT DIST 47.06 ANGLE 90, bears S. 71°37.0' E., 5.016 chs. dist.

- 39.972 The 1/4 section corner of sections 4 and 33, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap marked as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 63 E., executed by C.P. Sylvester in 1958, and a mound of stone south of the corner; add the marks 1993 to the cap.

From the corner of sections 4, 5, 32 and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked as described in the field notes of the independent resurvey of the subdivisional lines of T. 17 S., R. 63 E., executed by C.P. Sylvester in 1958, and a mound of stone south of the corner; add the marks 1993 to the cap.