

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 42 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T12N R42E S36 $\frac{1}{4}$ ——— S 1 T11N 1996</p> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>WEST, beginning new measurement.</p> <p>Over rolling mountainous land.</p>
39.150	<p>Point selected for the witness cor. to the cor. of secs. 1, 2, 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">WC T12N R42E S35 S36 ←— — S 2 S 1 T11N 1996</p>
40.000	<p>Point for the cor. of secs. 1, 2, 35 and 36, determined at record bearing and distance, falls on sheer face of 30 ft. vertical rock ledge where it is impossible to establish a permanent monument; there is no remaining evidence of the original corner.</p>
<p>DEPENDENT AND INDEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 12 N., R. 42 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of the Survey Executed by A. J. Hatch, D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors, in 1873</p> <hr/>	
<p>From the cor. of secs. 1, 2, 35 and 36, monumented with a granite stone, 16x8x6 ins., plainly mkd. with 1 groove on E. face and 5 grooves on W. face, loosely set in a mound of earth. This cor. will now refer to the cor. of secs. 1 and 2 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	