DEPENDENT AND INDEPENDENT RESURVEY OF A PORTION
OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 42 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.000	Point for the $^1/_4$ sec. cor. of secs. 1 and 12, NORTH 0.2 lks. from the tangent.

Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

<div align="center">

T12N R42E

S 1

$^1/_4$ ─────

S12

1997
</div>

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

From this corner, a rebar, $^5/_8$ in. diam., firmly set flush in ground, with yellow plastic cap, 1 in. diam., mkd. "M. MILLER PLS 6636" ($^1/_4$ sec. cor. of secs. 12 and 13), as recorded in Nye County, Nevada, file no. 263038, bears N. 72°22' W., 0.538 chs. dist.

48.10	Trail road, bears ESE. and WNW.
78.976	Intersect the W. bdy. of sec. 7, T. 12 N., R. 43 E. (Reese River Guide Meridian).

Point for the closing cor. of secs. 1 and 12, NORTH 0.8 lks. from the tangent.

Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

<div align="center">

T12N | T12N

S 1 | R43E

CC─────|

S12 | S 7

R42E |

1997
</div>

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

From this corner, the cor. of secs. 7 and 18 only, T. 12 N., R. 43 E., hereinbefore described, bears S. 0°47'00" W., 0.331 chs. dist.

The point for the $^1/_4$ sec. cor. of sec. 12 only, is at midpoint between closing corners and on the W. bdy. of sec. 18, T. 12 N., R. 43 E.

Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

<div align="center">

T12N

R42E | R43E

$^1/_4$

S12 |

1997
</div>

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.