

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of the Survey Executed by R.H. Woods and W.H. Myrick in 1881 and the Resurvey Executed by N.R. Forsyth in 1990</p> <hr/> <p>Beginning at the S 1/16 sec. cor. of secs. 19 and 24, monumented with a stainless steel post, 2¹/₂ ins. diam., firmly set projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1990 resurvey.</p> <p>N. 0°19'40" E., bet. secs. 19 and 24.</p> <p>18.985 Intersect VTN center line of sec. 24 as shown on Record of Survey File 52, Page 70, on file in the office of the Clark County Recorder.</p> <p>Point for Angle Point No. 3, monumented with a rebar, ⁵/₈ in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd.: NORTH LAS VEGAS SURVEY MONUMENT PLS 9399; this monument was set by Larry E. Crow, City of North Las Vegas Surveyor, as shown on Record of Survey File 74, Page 46, on file in the office of the Clark County Recorder. This is accepted as a careful and faithful establishment of the intersection point.</p> <p>From this point, a rebar, ⁵/₈ in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd.: VTN PLS 6201, set by Gene D. Krametbauer as shown on Record of Survey File 52, Page 70, on file in the office of the Clark County Recorder, bears N. 87°16'50" E., 3.251 chs. dist.</p> <p>20.595 The 1/4 sec. cor. of secs. 19 and 24, monumented with a stainless steel post, 2¹/₂ ins. diam., firmly set projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1990 resurvey.</p>
	<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 24, T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by R.A. Pratt in 1990</p> <hr/> <p>From the ¹/₄ sec. cor. of secs. 19 and 24, hereinbefore described. S. 86°04'30" W., on the E-W center line of sec. 24.</p> <p>19.153 The C-E 1/16 sec. cor., monumented with a stainless steel post, 2¹/₂ ins. diam., firmly set projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1990 survey.</p> <p>From this corner, a rebar, ⁵/₈ in. diam., hereinafter described, bears S. 67°22'20" E., 2.814 chs. dist. (Record, S. 67°23' E.)</p> <hr/> <p>From the SE 1/16 sec. cor., monumented with a stainless steel post, 2¹/₂ ins. diam., firmly set projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1990 survey.</p>