## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 24, T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 19 S., R. OU E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	From this corner, a rebar, $^{5}/_{8}$ in. diam., hereinafter described, bears S. 74°36′50" E., 3.125 chs. dist. (Record, S. 74°30′ E., 2.394 chs.)
	N. 0°27'30" E., on the N-S center line of the SE1/4 of sec. 24.
20.437	The C-E 1/16 sec. cor.
	From the S 1/16 sec. cor. of secs. 19 and 24, hereinbefore described.
	S. 86°33'10" W., on the E-W center line of the SE1/4 of sec. 24.
16.183	Intersect VTN N-S center line of the SE1/4 as shown on Record of Survey File 52, Page 70, on file in the office of the Clark County Recorder.
	Point for Angle Point No. 1.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	AP1   S24 S = S24
	1997
	From this point, a rebar, ${}^{5}/_{8}$ in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd.: VTN PLS 6201, set by Gene D. Krametbauer as shown on Record of Survey File 52, Page 70, on file in the office of the Clark County Recorder, bears S. 00°43′00" E., 1.010 chs. dist.
19.189	The SE 1/16 sec. cor.
	METES-AND-BOUNDS SURVEY IN SECTION 24, T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA
	From Angle Point No. 1, hereinbefore described.
	N. 0°43′00" W., on line 1-2, on a portion of VTN N-S center line of the $SE^1/_4$ of sec. 24.
19.174	Point for Angle Point No. 2, monumented with a rebar, $^{5}/_{8}$ in. diam., firmly set 4 ins. below the surface of the ground at the intersection of Deer Spring Way and Thom Blvd., with aluminum cap mkd.: VTN PLS 6201, set by Gene D. Krametbauer as shown on Record of Survey File 52, Page 70, on file in the office of the Clark County Recorder.
	N. 87°16′50" E., on line 2-3, on a portion of VTN E-W center line of sec. 24.
16.519	Angle Point No. 3, hereinbefore described.