

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 41 N., R. 23 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Reestablishment of the Survey Executed by G.W. Garside and C.S. Preble, U.S. Deputy Surveyors, in 1874, and the Survey Executed by G.W. Garside, U.S. Deputy Surveyor, in 1877</p> <hr/> <p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set showing 16 ins. above the ground, with brass cap mkd. as described in the field notes of T. 40 N., R. 23 E., executed under Group No. 48, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>N. 1°22'50" E., bet. secs. 35 and 36.</p> <p>Over rolling land, covered with medium sagebrush, scattered rabbitbrush and native grass.</p>								
4.50	Wash, 10 lks. wide, 1 ft. deep, drains W.								
40.809	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 3 ft. base to top, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T41N R23E</td></tr> <tr><td colspan="2" style="text-align: center;">$\frac{1}{4}$</td></tr> <tr><td style="text-align: center;">S35</td><td style="text-align: center;"> S36</td></tr> <tr><td colspan="2" style="text-align: center;">1997</td></tr> </table>	T41N R23E		$\frac{1}{4}$		S35	S36	1997	
T41N R23E									
$\frac{1}{4}$									
S35	S36								
1997									
81.618	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T41N R23E</td></tr> <tr><td style="text-align: center;">S26</td><td style="text-align: center;"> S25</td></tr> <tr><td style="text-align: center;">S35</td><td style="text-align: center;"> S36</td></tr> <tr><td colspan="2" style="text-align: center;">1997</td></tr> </table>	T41N R23E		S26	S25	S35	S36	1997	
T41N R23E									
S26	S25								
S35	S36								
1997									
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>								
	<p>From the cor. of secs. 25 and 36, on the E. bdy. of the Tp.</p> <p>S. 88°20'20" W., bet. secs. 25 and 36.</p>								
41.009	<p>Over rolling land, covered with medium sagebrush, scattered rabbitbrush and native grass.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 3 ft. base to top, with brass cap mkd.</p>								