

DEPENDENT RESURVEY OF A PORTION OF  
THE FIFTH STANDARD PARALLEL SOUTH ON THE SOUTH BOUNDARY,  
T. 20 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by T. Binge in 1881</p> <hr/> <p>Beginning at the standard cor. of secs. 33 and 34 on the south boundary of the Tp., monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd.: VTN ENG CO RLS 2050; this monument was set by Kay L. Adams in 1973 as shown on Record of Survey File 26, Page 29, on file in the office of the Clark County Recorder. This is accepted as a careful and faithful remonumentation of the original corner.</p> <p>From this corner the closing corner of secs. 3 and 4, T. 21 S., R. 54 E., monumented with a metal tag mkd. RE 305, set in a concrete post, 6 ins. diam., flush with the surface of the ground, as shown on Record of Survey File 26, Page 29, on file in the office of the Clark County Recorder, bears N. <math>89^{\circ}26'40''</math> E., 2.344 chs. dist.</p> <p>S. <math>89^{\circ}46'20''</math> W., on the south boundary of sec. 33.</p> <p>39.832 The standard <math>\frac{1}{4}</math> sec. cor. of sec. 33 on the south boundary of the Tp., monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set 4 ins. below the surface of Gamebird Road, with aluminum cap mkd.: RL HAFEN RLS 4428; no map record of this monument was found; it is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>From this corner the standard cor. of secs. 32 and 33 on the south boundary of the Tp., hereinafter described, bears S. <math>89^{\circ}46'50''</math> W., 39.834 chs. dist.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 20 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by T. Binge in 1881</p> <hr/> <p>From the standard cor. of secs. 33 and 34 on the south boundary of the Tp., hereinbefore described.</p> <p>N. <math>3^{\circ}21'50''</math> E., bet. secs. 33 and 34.</p> <p>5.00 Nevada State Highway No. 160, NW-SE.</p> <p>11.00 Power transmission line, NW-SE.</p> <p>20.298 The S <math>\frac{1}{16}</math> sec. cor. of secs. 33 and 34, monumented with a rebar, <math>\frac{5}{8}</math> in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd.: VTN ENG CO RLS 2050; no map record of this monument was found; it is accepted as a careful and faithful establishment of the corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>
--------	---