

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

| | |
|---|--|
| CHAINS | |
| 32.80 | Power transmission line, NW-SE. |
| 35.80 | Power transmission line, NW-SE. |
| 40.884 | <p>The cor. of secs. 28, 29, 32, and 33, monumented with a stainless steel post, 2¹/₂ ins. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the 1990 resurvey.</p> <p>Corner is located in a fence which bears E-W.</p> |
| <hr/> <p>Reestablishment of the Survey Executed by T. Binge in 1881</p> <hr/> | |
| <p>From the cor. of secs. 27, 28, 33, and 34, hereinbefore described.</p> <p>S. 89°56'20" W., bet. secs. 28 and 33.</p> | |
| 40.850 | <p>The 1/4 sec. cor. of secs. 28 and 33, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd.: VTN ENG CO RLS 2050; no map record of this monument was found; it is accepted as a careful and faithful remonumentation of the original corner. A granite stone, 14x12x10 ins., mkd. 1/4, was found lying alongside the rebar.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20S R54E</p> <p>S28</p> <p>1/4 ———</p> <p>S33</p> <p>1997</p> </div> <p>Deposit the rebar inside and the mkd. stone alongside the stainless steel post.</p> |
| <hr/> <p>N. 89°39'00" W., beginning new measurement.</p> | |
| 18.40 | Graded road, NE-SW. |
| 40.518 | The cor. of secs. 28, 29, 32, and 33, hereinbefore described. |
| <hr/> <p>SUBDIVISION OF SECTION 33, T. 20 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> | |
| <p>From the standard 1/4 sec. cor. of sec. 33 on the south boundary of the Tp., hereinbefore described.</p> | |
| <p>N. 0°47'20" E., on the N-S center line of sec. 33.</p> | |