DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 39 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 39 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	T39N R27E
	s 6 s 5
	1997
	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
81.10	Spur, slopes SSE.
86.509	The cor. of secs. 5 and 6, on the N. bdy. of the Tp.
	SUBDIVISION OF SECTION 6, T. 39 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
, in the second second	N. 0°06'10" W., on the N-S center line of sec. 6.
	Over native hay meadow.
16.20	Ditch, 3 lks. wide, with water 18 ins. deep in bottom of ditch, courses irregularly SE.
18.20	Bluff, bears irregularly SE. and NW.; enter rolling land.
20.20	Trail road, bears irregularly SE. and NW.
20.953	Point for the C-S $^{1}/_{16}$ sec. cor. of sec. 6.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$S^{-1}/_{16}$ $\begin{bmatrix} C \\ S \end{bmatrix}$ G
	1997
	Set a steel fence post, $5^1/_2$ ft. long, alongside the stainless steel post.
22.50	Fence, bears SE. and NW.
23.00	Bladed road, parallels fence.
41.906	Point for the center $^1/_4$ sec. cor. of sec. 6, at intersection with the E-W center line of sec. 6.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T39N R27E $C^{-1}/_4$ S 6
	1997