## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 10 N., R. 20 E., MOUNI DIABLO MERIDIAN, NEVADA
CHAINS	(Reestablishment of a Portion of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, $2^1/2$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 29 E., executed concurrently under this same group.
	S. 89°45'10" W., bet. secs. 1 and 12.
	Over rolling land, covered with scattered greasewood and shadscale.
40.166	The $^{1}/_{4}$ sec. cor. of secs. 1 and 12, perpetuated by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, monumented with a rebar, $^{5}/_{8}$ in. diam., 2 ft. long, firmly set in a mound of stone, with a plastic cap, 1 in. diam., mkd. "FITZPATRICK PLS 7809", with the original monument, a basalt stone, 15X9X6 ins., mkd. $^{1}/_{4}$ on one of the faces, lying alongside, as shown on an unrecorded plat.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T16N R28E  S 1  1/4 —— S 12
	1996
	Deposit the original cornerstone alongside the stainless steel post, insert the rebar inside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	N. 88°18'40" W., beginning new measurement.
	Over alkali flat.
40.343	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T16N R28E
	S 2   S 1
	S11 S12
	1996
	Set a steel fence post, 5 ft. long, alongside the stainless steel post.