

042

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

(Reestablishment of the Survey Executed by  
M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)

From the cor. of secs. 1, 6, 7 and 12, perpetuated by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, monumented with a rebar, 2 ft. long,  $\frac{5}{8}$  in. diam., firmly set in a mound of stone, with a plastic cap, 1 in. diam., mkd. "FITZPATRICK PLS 7809", with the original monument, a basalt stone, 14X9X4 ins., mkd. with 5 grooves on one face and 1 groove on opposite face, lying alongside, as shown on an unrecorded plat.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T16N	
R28E	R29E
S 1	S 6
<hr/>	
S12	S 7

1996

Deposit the original cornerstone alongside the stainless steel post, insert the rebar inside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N.  $0^{\circ}19'20''$  W., bet. secs. 1 and 6.

Over gently rolling land, covered with scattered shadscale and greasewood.

16.60 Enter bottom land, covered with scattered shadscale, greasewood and native grass.

28.30 Canal, 30 lks. wide, 3 ft. deep, bears ESE. and WNW.

28.50 Bladed road, parallels canal.

39.757 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, monumented with a basalt stone, 18X12X8 ins., dimly mkd.  $\frac{1}{4}$  on W. face, firmly set in a mound of earth.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T16N	
R28E	R29E
$\frac{1}{4}$	
S 1	S 6

1996

Deposit the original cornerstone and set a steel fence post, 5 ft. long, alongside the stainless steel post.