


043

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	NORTH, beginning new measurement.						
29.000	<p>Point for the meander cor. of secs. 1 and 6, determined at record bearing and distance; there is no remaining evidence of the original corner. This cor. will now function as the meander cor. of sec. 6 only, and also as Angle Pt. No. 3, Tract 38.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>MC S 6 R28E R29E T16N</p> </div> <p>1998</p> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 16 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>(Reestablishment of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp. N. 89°17'10" W., bet. secs. 1 and 12.</p> <p>Over rolling land, covered with scattered shadscale, greasewood and native grass.</p> <tr> <td>1.70</td><td>Wash, 10 lks. wide, 1 ft. deep, drains irregularly NE.</td></tr> <tr> <td>6.20</td><td>Fence, bears ENE. and WSW.</td></tr> <tr> <td>40.194</td><td> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, monumented with a basalt stone, 18X8X8 ins., mkd. <math>\frac{1}{4}</math> on S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R29E S 1 1/4 ——— S12</p> <p>1996</p> </div> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> </td></tr>	1.70	Wash, 10 lks. wide, 1 ft. deep, drains irregularly NE.	6.20	Fence, bears ENE. and WSW.	40.194	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, monumented with a basalt stone, 18X8X8 ins., mkd. <math>\frac{1}{4}</math> on S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R29E S 1 1/4 ——— S12</p> <p>1996</p> </div> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>
1.70	Wash, 10 lks. wide, 1 ft. deep, drains irregularly NE.						
6.20	Fence, bears ENE. and WSW.						
40.194	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, monumented with a basalt stone, 18X8X8 ins., mkd. <math>\frac{1}{4}</math> on S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T16N R29E S 1 1/4 ——— S12</p> <p>1996</p> </div> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>						