DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 17 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 17 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	(Reestablishment of the Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881, and the Retracement and Resurvey Executed by W.A. Prey, U.S. Surveyor, in 1912)
	From the cor. of Tps. 17 and 18 N., Rs. 29 and 30 E., identical with Angle Pt. No. 1, Tract 37, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 17 N., R. 30 E., executed concurrently under this same group.
	N. 89°45'50" W., on the S. bdy. of sec. 36, T. 18 N., R. 29 E., identical with line 1-2, Tract 37.
	Along fence, over pasture land, covered with native grass.
40.097	The $^{1}/_{4}$ sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set flush with the surface of the ground, in fence, bears E. and W., with brass cap mkd. as described in the field notes of T. 18 N., R. 29 E., executed under Group No. 16. This cor. will now function as the $^{1}/_{4}$ sec. cor. of sec. 36 only, and also as Angle Pt. No. 2, Tract 37.
	Remark the brass cap to read
	T18N R29E 1/4 S36
	T17N
	1998 1912
	N. 89°46'20" W., beginning new measurement, identical with line 2-3, Tract 37.
0.10	Corner of fences, bears N. and E.
39.60	Canal, 30 lks. wide, 4 ft. deep, bears N. and S.
40.068	The cor. of secs. 1, 2, 35 and 36, monumented with remains of an iron post, 12 ins. long, 1 in. diam., filled with concrete, firmly set flush with the surface of the ground. This cor. will now function as the cor. of secs. 35 and 36 only, and also as Angle Pt. No. 3, Tract 37.
Maria de la Carta	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 6 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.
Nanika symusy verifica mate	
Tension and the second	