

070

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 17 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 39.90</p>	<p>Pasture Road, parallels power line.</p>
<p>40.159</p>	<p>The cor. of secs. 3, 4, 33 and 34, determined by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, as recorded in Churchill County, Nevada, Book 1, Page 48 of Surveys, subsequently remonumented by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, monumented with a rebar, $\frac{5}{8}$ in. diam., firmly set 4 ins. below the surface of the ground, on W. shoulder of Pasture Road, with a plastic cap, 1 in. diam., mkd. "FITZPATRICK RLS 7809" as recorded in Churchill County, Nevada, Book 17, Page 30 of Surveys. This position has been adopted by professional land surveyors and is accepted as the best available evidence of the position of the original corner. Point not remonumented.</p> <p>From this corner, the cor. of secs. 4, 5, 32 and 33, bears N. 89°55'10" W., 80.384 chs. dist., monumented with an iron post, 3 ins. diam., firmly set 10 ins. below the surface of dirt road, bears N. and S., with brass cap mkd. as described in the field notes of T. 18 N., R. 29 E., executed under Group No. 16.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>(Reestablishment of the Survey Executed by E.B. Monroe and A.G. Bateman, U.S. Deputy Surveyors, in 1874, and the Resurvey and Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., identical with Angle Pt. No. 1, Parcel A, T. 17 N., R. 28 E.</p> <p>N. 89°57'00" E., bet. secs. 18 and 19.</p> <p>Over level land, along fence.</p>
<p>40.000</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, determined latitudinally by a fence extending E. and W. and longitudinally by proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17N R29E S18 1/4 ——— S19 1998</p> <p>Cor. is located 1.25 chs. S. 65° W. of a canal, 23 lks. wide, bears N., E. and W. and 0.30 chs. N. of a canal, 15 lks. wide, bears E. and W.</p> <hr/> <p>N. 89°58'10" E., beginning new measurement.</p>
<p>0.81</p>	<p>Corner of fences, bears N., E. and W.</p>