DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 17 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

	·
CHAINS	(Reestablishment of the Survey Executed by E.B. Monroe, U.S. Deputy Surveyor, in 1868, and the Resurvey and Survey Executed by M.F. Reilly and T.A. Magee, U.S. Deputy Surveyors, in 1881)
	From the $^{1}/_{4}$ sec. cor. of secs. 4 and 33, monumented with a basalt stone, 16X12X8 ins., mkd. $^{1}/_{4}$ on S. face, firmly set in a mound of stone. This cor. will now function as the $^{1}/_{4}$ sec. cor. of sec. 33 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.
	T17N R30E ¹ / ₄ S33
	T16N R30E
	1996
	Deposit the original cornerstone alongside the stainless steel post.
	N. 89°46'40" W., on the S. bdy. of sec. 33.
	Over rolling land, covered with scattered shadscale and greasewood.
17.60	Buried gas line, bears S. $32^{1}/_{2}^{\circ}$ E. and N. $32^{1}/_{2}^{\circ}$ W.
17.75	Trail road, parallels gas line.
33.183	The closing cor. of secs. 4 and 5, T. 16 N., R. 30 E., monumented with a stainless steel post, $2^{1}/_{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 16 N., R. 30 E., executed concurrently under this same group.
40.210	The cor. of secs. 4, 5, 32 and 33, monumented with a basalt stone, 15X9X4 ins., mkd. with 4 grooves on E. face and 2 grooves on W. face, firmly set in a mound of stone. This cor. will now function as the cor. of secs. 32 and 33 only.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2^1/_2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T17N R30E S32 S33
	S 5 T16N
	1996