DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 23 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 25 S., R. GZ E., HOURT DIRECT REKEDENT, ADVIDER
CHAINS	Reestablishment of the Survey Executed by T.A. Magee in 1883 and the Resurvey Executed by E. Voigt and J.W. Hardison in 1942-43
	Beginning at the cor. of secs. 4, 5, 32, and 33, on the north boundary of the Tp., monumented with an iron post, 2 in. diam., set in a mound of stone, with brass cap mkd. as described in the field notes of the 1942-43 resurvey.
	N. 89°35'40" W., bet. secs. 5 and 32.
40.022	The $^{1}/_{4}$ sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap mkd. as described in the field notes of the 1942-43 resurvey.
	N. 89°35'20" W., beginning new measurement.
19.974	The W $^1/_{16}$ sec. cor. of secs. 5 and 32, monumented with a rebar, $^5/_8$ in. diam., set flush with the surface of the ground, with aluminum cap mkd.
	G C WALLACE INC
	PAUL BURN
	T22S R62E S32
	W 1/16 ——
	S 5
	T23S PLS 11174
	1998
	This monument was set by Paul Burn in 1998 as shown on Record of Survey File 99, Page 71, on file in the office of the Clark County Recorder and is accepted as a careful and faithful determination of the corner position.
	N. 89°35'20" W., beginning new measurement.
9.986	The W-W $^{1}/_{64}$ sec. cor. of secs. 5 and 32, monumented with a rebar, $^{5}/_{8}$ in. diam., set flush with the surface of the ground, with aluminum cap mkd.
	G C WALLACE INC
	PAUL BURN T22S
	S32
	W-W 1/64
	S 5 T23S R62E
	PLS 11174
	1998
	This monument was set by Paul Burn in 1998 as shown on Record of Survey File 99, Page 71, on file in the office of the Clark County Recorder and is accepted as a careful and faithful determination of the corner position.