

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

| CHAINS | <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.C. Smyles and A.J. Hatch in 1872, and a Portion of the Dependent Resurvey and Completion Survey Executed by J.B. Menardi in 1905</p> | | | | | | |
|---------------|---|------|------|---------------|-----|-----|-----|
| | <p>From the cor. of secs. 13, 14, 23 and 24, monumented with an iron rebar, $\frac{5}{8}$ in. diam., 12 ins. long, firmly set projecting 2 ins. above the ground, with a metal washer, 1 in. diam., mkd. "LS 1797", attached to the iron rebar, with the original monument, a basalt stone, 17X10X5 ins., mkd. 1 notch on an edge and 3 notches on an adjacent edge, lying alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, over a plastic-encased magnet and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="878 768 1024 873"> <tr> <td>T20N</td><td>R20E</td></tr> <tr> <td>S14</td><td>S13</td></tr> <tr> <td>S23</td><td>S24</td></tr> </table> <p>1999</p> <p>Deposit the original cornerstone alongside the stainless steel post and insert the iron rebar inside the stainless steel post.</p> <p>Corner is located at corner of fences, bearing E., W. and S.</p> <p>From this corner, U.S. Coast and Geodetic Survey triangulation station "ROCKY", bears S. $13^{\circ}25'47''$ E. (mean bearing), 377.432 chs. dist., monumented with a standard brass tablet, firmly set in a rock outcrop, mkd. "ROCKY 1946".</p> <p>N. $0^{\circ}09'30''$ W., bet. secs. 13 and 14.</p> <p>Over mountainous land covered with medium sagebrush, scattered rabbitbrush and native grass.</p> | T20N | R20E | S14 | S13 | S23 | S24 |
| T20N | R20E | | | | | | |
| S14 | S13 | | | | | | |
| S23 | S24 | | | | | | |
| 40.160 | <p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a basalt stone, 19X12X9 ins., firmly set projecting 6 ins. above the ground, mkd. $\frac{1}{4}$ on W. face and a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table border="1" data-bbox="878 1614 1024 1698"> <tr> <td>T20N</td><td>R20E</td></tr> <tr> <td>$\frac{1}{4}$</td><td></td></tr> <tr> <td>S14</td><td>S13</td></tr> </table> <p>1999</p> <p>Deposit the original cornerstone alongside the stainless steel post.</p> | T20N | R20E | $\frac{1}{4}$ | | S14 | S13 |
| T20N | R20E | | | | | | |
| $\frac{1}{4}$ | | | | | | | |
| S14 | S13 | | | | | | |